

imageRUNNER iR2520i/iR2525i

Next generation document communication

The imageRUNNER iR2520i and iR2525i are versatile, high quality monochrome multi-functional printers designed to improve document communications in small, medium and home offices utilising their innovative product solutions.

At a glance...

- iR2520i prints 20 monochrome prints per minute.
- iR2525i prints 25 monochrome prints per minute.
- Versatile paper handling and finishing.
- 1200 x 1200dpi printing.
- Simple and easy to use design.

Productivity

- Print speeds of 20 and 25 pages per minute.
- Save time with automatic document feeders.
- Change paper less often with high capacity paper drawers.

Cost Saving

- Reduce paper usage with Duplex printing.

Usability

- Scan and transport documents directly to USB.
- Print with ease by directly printing from your USB.
- Scan and send documents easily using Colour Send.
- Create address books from 1,000 destinations using LDAP server.
- Finish documents in the machine with the internal finisher (optional).
- Utilise different types and sizes of paper with multiple drawers and paper feeding options.
- Print when the document doesn't match the paper in the machine with Force Print.

Quality

- Create first class prints with 1200 x 1200 dpi print quality.
- Scan with precision by utilising the CIS technology.

Integration

- Postscript and PCL to fit in with your IT systems (optional).



Specifications

Type	Desktop (Reader/Printer separated)		
Maximum Original Size	A3		
Copy Sizes	Cassette	A3/ A4/ A4R/ A5R/ B4/ B5/ B5R LDR/ LGL/ LTR/ LTRR/ STMTR/ EXEC 8K/16K/16KR K-LGL / K-LGL-R OFFICIO/E OFFICIO/B OFFICIO/M OFFICIO/A OFFICIO A LTR / A LTRR / G LTR / G LTRR /G LGL / FLS / A FLS / F4A COM10.Monarch.ISO-C5.ISO-B5.DLB=the optional envelope feeder attachment-D1 is required	
	Stack Bypass	A3/A4/A4R/A5R/B4/B5/B5R LDR/LGL/LTR/LTRR/STMTR/EXEC 8K/16K/16KR K-LGL / K-LGL-R OFFICIO/E OFFICIO/B OFFICIO/M OFFICIO/A OFFICIO A LTR / A LTRR / G LTR / G LTRR /G LGL / FLS / A FLS / F4A COM10.Monarch.ISO-C5.ISO-B5.DL,	
Resolution	Reading	600dpi x 600dpi	
	Copying	600dpi x 600dpi	
	Printing	1200dpi x 1200dpi (text/line only) 256 Gradations	
Copy/Print Speed	A4	iR2520i: Up to 20ppm (B&W) iR2525i: Up to 25ppm (B&W)	
	A3	iR2520i: Up to 15ppm (B&W) iR2525i: Up to 15ppm (B&W)	
Magnification	Zoom	25-400%	
	Fixed	25%, 50%, 70%, 81%, 86%, 115%, 122%, 100%, 141%, 200%, 400%	
First copy time	Black-and-White	iR2520i: 6.4 sec or less iR2525i: 5.4 sec or less	
Warm-Up Time	30 seconds		
Multiple Copies/Prints	1 to 999 sheets		
Duplexing	Standard automatic stackless		
Paper weight	Cassette	64-90gsm (iR2520i/iR2525i)	
	Stack Bypass	64-128gsm	
	Duplex	64-90gsm (iR2520i/iR2525i)	
Paper Capacity	Standard	550 sheets x 2 cassettes + stack bypass 100 sheets (80gsm) (iR2525i) 250 sheets x 1 cassette + stack bypass 100 sheets (80gsm) Optional Cassettes: 550 sheets x 2 cassettes (80gsm)	
	Max capacity	2,300 sheets	
CPU	Canon Custom Processor, 400MHz		
Memory	512MB		
Interface	Ethernet (100Base-TX/10Base-T), USB Host I/F 2.0 x 1 port, USB Device 1.0 x 1 port		
Power Supply	220-240V AC, 50/60Hz, 3.3A		
Power Consumption		1.345kW (25ppm), 1.542kW (20ppm)	
	Sleep Mode	1.5W = OK	
Dimensions (WxDxH)	imageRUNNER iR2525i: 565 mm x 689 mm x 896 mm imageRUNNER iR2520i: 565 mm x 693 mm x 771 mm		
Weight	imageRUNNER iR2525i: Approx. 77.5 kg imageRUNNER iR2520i: Approx. 58.9 kg		
Print Specification (Standard)			
PDL	UFRII-LT, PCL5e/6 (optional), PostScript level 3 emulation (optional)		
Resolution	600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)		
Memory	512MB		
CPU	Canon Custom Processor, 400MHz		
PS Fonts (optional)	Roman 136		
PCL Fonts (optional)	Roman 93		
Supported OS	PCL	Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7	
	Adobe PostScript 3	Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later)	
	UFR II	Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later), Linux	
	Mac-PPD	Mac-PPD: Mac OS X 10.4 or later	
Interface	Ethernet (100Base-TX/10Base-T)		
Network Protocol	TCP/IP(LPD/ Port9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support		
Pull Scan	Network TWAIN Driver (75/ 100/ 150/ 200/ 300dpi 8bit color / 75-600dpi 1bit Black & white)		
Send Specification			
Scan Speed (A4, 300dpi)	25/25ipm(25/ 20 ppm model) 300dpi		
Scan Resolution	BW: 100 x 100 dpi, 150 x 150 dpi, 200 x 100dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi CL:100 x 100 dpi,150 x 150 dpi, 200 x 200 dpi, 300 x 300dpi		
Destinations	E-Mail/ Internet FAX(SMTP), PC/Server (SMB,FTP), iWDM, USB memory key		
Address book	LDAP, Local (Max.500)		
File Format	TIFF, JPEG, PDF, High compression PDF		

PDF High Compression Kit

Model Name	SEARCHABLE PDF-C1
Format	Searchable PDF (optional)
DADF	
Standard	DADF-AB1
Paper size	A3, A4, A4R, A5, A5R Custom size 148 to 297mm x 128 to 432mm
Paper weight	Single sided original: 52 to 105 g/m2 Double sided original: 52 to 105 g/m2
Max Number of Originals	50 sheets (A4, A4R, A5, A5R: 80 g/m2), 25 sheets (A3: 80 g/m2)
Document Scanning Speed	imageRUNNER iR2525i: Copy: 25ipm (A4, 600 x 600 dpi: BW) Scan: 25/25 ipm (A4, 600 x 600 dpi:BW / 300 x 300 dpi: Colour) imageRUNNER iR2520i: Copy: 20ipm (A4, 600 x 600 dpi: BW) Scan: 25/25 ipm (A4, 600 x 600 dpi:BW / 300 x 300 dpi: Colour) 565 mm x 544 mm x 126 mm Approx. 7.0 kg
Dimensions	
Weight	

Cassette Feeding Module

Model Name	CASSETTE UNIT-W1 for imageRUNNER iR2520i CST. Feeding UNIT-AE1 for all models imageRUNNER iR2520i: Front-loading adjustable drawers all models: 2 Front-loading adjustable drawers
Paper Weight	imageRUNNER iR2520i/i: 64 to 90g/m2 all models: 64 to 90 g/m2
Paper Capacity	imageRUNNER iR2520i: 550 sheets (80 g/m2) x 1 cassette all models: 550 sheets(80 g/m2) x 2 cassettes
Dimensions (W x D x H)	imageRUNNER iR2520i: 565 mm x 680 mm x 97 mm all models: 565 mm x 680 mm x 248 mm
Weight	imageRUNNER iR2520i: Approx. 12.8kg all models: Approx. 24.0kg

Finisher

Optional	Inner Finisher-B1 for all models
Number of Trays	
Tray Capacity	One stack tray (Optional 2nd Tray:INNER FIN ADD. TRAY-B1) A4 - A5R :1000 sheets (or 125 mm in height) A3, A4R: 500 sheets (or 62.5 mm in height) max 297 x 432mm, A3, A4R
Staple Position	Corner, Double
Staple Capacity	A4: 50 sheets x 30 sets A4R/ A3: 30 sheets x 15 sets

Inner 2-way Tray

Tray Capacity	Tray A - A4: 250 sheets, A3: 100 sheets Tray B - A4:100 sheets, A3: 50 sheets
---------------	--

Weight

Approx. 0.6kg

Other Optional Accessories

PCL PRT KIT-AF1, PS PRT KIT-AF1, BARCODE PRINTING KIT-B1, CASSETTE SPACER-A1, PEDESTAL LOW HEIGHT 248 MM FOR iRiR2525i/2535i/2545i, PEDESTAL HIGH HEIGHT 373 MM FOR iRiR2520i, ENVELOPE ATCHMT-D1, FL CASSETTE-AJ1(M), FL CASSETTE-AK1(L), FL CASSETTE-AL1(250), READER HTR-H1 200V, DRUM HEATER-C1, HEATER KIT-J1 200V, CST. HEATER UNIT-37, USB APP 3-PORT I/F-A1, CONTROL I/F CABLE-A1, STAMP UNIT-B1,

TM All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon reserves the right to change specifications without notice.



Australia call: 1800 444 199
New Zealand call: 0800 222 666